


KANN

Measuring Instruments Catalog



KANN

PRECISION MEASURING INSTRUMENTS CO.

IN TODAY'S HIGHLY COMPETITIVE BUSINESS, THE TECHNICAL REQUIREMENTS DEMAND THE UTMOST PRECISION AT ALL STAGES OF MANUFACTURE OF A PRODUCT. TO COMPLY WITH THESE REQUIREMENTS, PRECISION MEASURING INSTRUMENTS HAVE BECOME AN INDESPENSIBLE PART OF EVERYDAY EQUIPMENT.



MANUFACTURES PRECISION DIAL INDICATORS & VARIOUS MEASURING INSTRUMENTS WITH THE FOLLOWING SALIENT FEATURES.

A SOLID RIGID OUTER CASE PROTECTS THE PRECISE INNER GEARING.

FIXING STEM IS STANDARD \varnothing 8mm h6,

MADE FROM STAINLESS STEEL & IS HARDENED & GROUND.

MOVEMENT IS FITTED ON THICK BRASS PLATE .

THE ROTATING OUTER DIAL WITH KNURLED BAZEL, ALLOWS ZERO SETTING IN ANY POSITION & IS FIXED IN POSITION BY A CLAMP.

MEASURING ACCURACY CONFIRMS TO IS: 2092, 1983 STANDARDS.

ASSURED SPARE PARTS SUPPLY & AFTER SALES SERVICE.

STANDARD DIAL GAUGES.

MODEL	DIAL DIA.	L.C.	RANGE	GRADUATION
M2/10	57mm	0.001mm	1mm	0 - 100 - 0
M2/11	80mm	0.001mm	1mm	0 - 100 - 0
M2/5/1	57mm	0.002mm	5mm	0 - 20
M8	57mm	0.005mm	5mm	0 - 50 - 0
M2	57mm	0.01mm	10mm	0 - 100
M3	57mm	0.01mm	10mm	0 - 50 - 0
M7	57mm	0.01mm	5mm	0 - 100
M5	57mm	0.02mm	10mm	0 - 100
M6	80mm	0.01mm	10mm	0 - 100
M10A	57mm	0.1mm	10mm	0 - 100



M2



M10A



M2/10



M2/5/1

ONE REVOLUTION DIAL GAUGES.

MODEL	DIAL DIA.	L.C.	RANGE	GRADUATION
M2/14	57mm	0.001mm	0.16mm	80 - 0 - 80
M2/12	80mm	0.001mm	0.16mm	80 - 0 - 80
M2/16	57mm	0.001mm	0.10mm	50 - 0 - 50
M2/15	80mm	0.001mm	0.10mm	50 - 0 - 50
M2/1	57mm	0.01mm	0.9mm	40 - 0 - 40
M2/2	57mm	0.01mm	1.6mm	80 - 0 - 80



M2/1



M2/14



M2/12



M2/15



Z2

INCH DIAL GAUGES

MODEL	DIAL DIA.	L.C.	RANGE	GRADUATION
Z2	57mm	0.001"	0.4"	0 - 100
Z3	57mm	0.001"	0.4"	0 - 50 - 0
Z2/25	57mm	0.001"	1"	0 - 100

MINIATURE DIAL GAUGES.

MODEL	DIAL DIA.	L.C.	RANGE	GRADUATION
M4	40mm	0.001mm	5mm	0 - 100
M4/1	40mm	0.001mm	5mm	0 - 50 - 0
M4/2	40mm	0.001mm	3mm	0 - 100
M4/3	40mm	0.001mm	3mm	0 - 50 - 0
Z4	40mm	0.001"	0.2"	0 - 100
Z5	40mm	0.001"	0.2"	0 - 50 - 0



M4

LONG RANGE DIAL GAUGES.

MODEL	DIAL DIA.	L.C.	RANGE	GRADUATION
M2/25	57mm	0.01mm	25mm	0 - 100
M2/30	57mm	0.01mm	30mm	0 - 100
M2/25/80	80mm	0.01mm	25mm	0 - 100
M2/30/80	80mm	0.01mm	30mm	0 - 100
M2/50	57mm	0.01mm	50mm	0 - 100
M2/50/80	80mm	0.01mm	50mm	0 - 100
M10C	57mm	0.1mm	30mm	0 - 10
M10D	57mm	0.1mm	30mm	0 - 10



M2/50



M10C



M2/30



M2/50/80

DIAL INDICATORS FOR HARDNESS TESTING MACHINES.


MODEL	DIAL DIA.	DESCRIPTION
A - 80	80mm	for rockwell machine with B & C Scale
AS - 80	80mm	for rockwell cum superficial machine
AH - 80	80mm	for brinell machine
A - 92	92mm	for rockwell machine with B & C scale
AS - 92	92mm	for rockwell cum superficial machine
RASN	95mm	for rockwell machine with B & C Scale (export model)
RASN - T	95mm	for rockwell cum superficial machine (export model)
O'	57mm	for optical machine



AS - 80



A - 80



RASN

DIAL THICKNESS GAUGES.


MODEL	DIAL DIA.	L.C.	RANGE	GRADUATION	ANVIL DIA.
T.G.1	57mm	0.01mm	10mm	0 - 100	6mm/10mm
T.G.2	57mm	0.001mm	1mm	0 - 100 - 0	6mm/10mm
T.G.3	57mm	0.1mm	10mm	0 - 10	6mm/10mm
T.G.4	57mm	0.01mm	10mm	0 - 100	6mm/10mm push down
T.G.5	57mm	0.1mm	25mm	0 - 10	10/20/25mm push down
T.G.6	57mm	0.01mm	10mm	0 - 100	pipe thickness gauge
T.G.7	57mm	0.1mm	30mm	0 - 10	10/20mm
T.G.8	57mm	0.01mm	25mm	0 - 100	6/10/20mm



T.G.5



T.G.1



T.G.7



T.G.6



T.G.4

DIGITAL DIAL THICKNESS

MODEL	L.C.	RANGE	ANVIL DIA.
E.T.G.1	0.01 mm	10 mm	6mm / 10mm
E.T.G.2	0.001mm	10mm	6mm / 10mm




E.T.G.1

PLEASE REFER TO OUR PRODUCT LIST FOR COMPLETE RANGE.

DEEP THROAT DIAL THICKNESS GAUGES.

MODEL	DIAL DIA.	L.C.	RANGE	GRADUATION	ANVIL DIA.
T.G.11	57mm	0.1mm	10mm	0 - 10	10/20/25mm
T.G.12	57mm	0.01mm	10mm	0 - 100	10/20mm
T.G.13	57mm	0.1mm	30mm	0 - 10	10/20/25mm
T.G.14	57mm	0.01mm	30mm	0 - 100	10/20mm



T.G.13

POCKET THICKNESS GAUGES.

MODEL	DIAL DIA.	L.C.	RANGE	GRADUATION	ANVIL DIA.
T.G.10		0.1mm	10mm	0 - 10	6mm / 10 mm
T.G.20		0.1mm	20mm	0 - 10 - 20	6 mm / 10 mm



T.G.10



T.G.20

DIAL GAUGE FOR AIR GAUGE UNIT.

MODEL	DIAL DIA.	L.C.	RANGE	GRADUATION
M1	105mm	0.01mm	1mm	40 - 0 - 40.



M1



RHT SHR A

DUROMETERS

MODEL	L.C.	RANGE
RHT SHR A	1 SHR	0 -100 SHR

Supplied with Test Block and Test Certificate.

SURFACE PROFILE GAUGE.

MODEL	GRADUATION	RANGE
SPG01	+/- 100	+/- 500 MICRONS.












DIGITAL MODEL ALSO AVAILABLE.

DIGITAL THICKNESS GAUGES.

MODEL	GRADUATION	RANGE
ETG1	0,01 mm	0 - 12 mm




PLEASE REFER TO OUR PRODUCT LIST FOR COMPLETE RANGE.



RACK EXTENSIONS.

Special anvils can be manufactured as per customers drawing.



ACCESSORIES
BACK COVER WITH LUG
FLAT BACK COVER (METAL)
LIFTING LEVER.
H.C.H.C. BALL ANVILS
CARBIDE BALL ANVILS
RUBY BALL ANVILS
ANVILS CP1 - CP8

KANN PRECISION MEASURING INSTRUMENTS CO.

A-3, NERGISH NIWAS, IRANI ROAD,
OPP. IDBI BANK , DAHANU - 401602.
DIST. PALGHAR, MAHARASHTRA, INDIA.

Call / Whatsapp on: +91 - 9850733755 / +91 - 9665575758

Email: kanngauges@gmail.com/ sales@kanngauges.com
Website: kanngauges.com/ kanngauges.in